



EU DECLARATION OF CONFORMITY

We, the undersigned,

BEA SA, LIEGE Science Park, Allée des Noisetiers, 5, 4031 Angleur, Belgium

declare that the declaration of conformity is issued under our sole responsibility and belongs to the following product(s):

CONDOR motion & presence sensor for industrial doors

The object of the declaration described above is in conformity with the relevant Union harmonisation legislation:

2014/53/EU RED Directive
2011/65/EU RoHS 2 Directive

The following harmonised standards and technical specifications have been applied:

EN 300 440-2 V1.4.1	Electromagnetic compatibility and Radio spectrum Matters (ERM); Short range devices; Radio equipment to be used in the 1 GHz to 40 GHz frequency range; Part 2: Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive
EN 301 489-1 V1.9.2	Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements
EN 301 489-3 V1.6.1	Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 3: Specific conditions for Short-Range Devices (SRD) operating on frequencies between 9 kHz and 246 GHz
EN 62311:2008	Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)
EN 62479:2010	Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)

Angleur, 12th June 2017
Pierre GARDIER
Chief Technology Officer
(authorized representative)

Angleur, 12th June 2017
Elmar KOCH
Managing Director



IMPORTANT INFORMATION CONCERNING THE USE OF THE TRANSMITTER

- Transmitter head characteristics:

Output frequency:	24.150 GHz
Transceiver Output Power:	< +7 dBm
Transceiver + Antenna EIRP:	< +20 dBm
Operating Voltage:	5V DC \pm 5 %
Operating Current:	80 mA typ.
Operating temperature range:	-30°C to +70°C

- Critical sealed adjustments not to be touched
- Allowed Antennas: Patch Antenna 3x1, 3x2, or 3x3

CONSTRAINTS CONCERNING THE USE OF RADIO EQUIPMENT IN THE EU

COUNTRY	OUTPUT POWER	FREQUENCY BAND	STATUS
AUSTRIA	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
BELGIUM	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
DENMARK	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
FINLAND	100 mW E.I.R.P.	24.000 – 24.250 GHz	NO LICENCE REQUIRED
FRANCE	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
GERMANY	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
GREECE	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
IRELAND	100 mW E.I.R.P.	24.000 – 24.250 GHz	NO LICENCE REQUIRED
ITALY	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
LUXEMBOURG	100 mW E.I.R.P.	24.000 – 24.250 GHz	NO LICENCE REQUIRED
NETHERLANDS	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
PORTUGAL	100 mW E.I.R.P.	24.000 – 24.250 GHz	NO LICENCE REQUIRED
SPAIN	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
SWEDEN	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
UNITED KINGDOM	100 mW E.I.R.P.	24.150 – 24.250 GHz	NO LICENCE REQUIRED
ICELAND	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
NORWAY	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
SWITZERLAND	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
CYPRUS	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
CZECH REPUBLIC	100 mW E.I.R.P.	24.000 – 24.250 GHz	NO LICENCE REQUIRED
ESTONIA	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
HUNGARIA	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
LITHUANIA	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
POLAND	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
SLOVAKIA	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
SLOVENIA	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
LATVIA	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED
MALTA	100 mW E.I.R.P.	24.050 – 24.250 GHz	NO LICENCE REQUIRED

SAFETY RELATED PRECAUTIONS

WARNING! This equipment must be powered by an EN 60950-1 approved Class II SELV and Limited Power Source. This requirement consists of the need for a double isolation between primary voltages and sensor power supply. The power supply current will be limited by a fuse rated between 0.5A and 3A. We recommend a value of 0.5A T.